

Earth-Moving Machinery

LW156FV Wheel Loader



- **Product Category:** Wheel Loader
- **Brand:** XCMG
- **Model:** LW156FV
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of LW156FV Wheel Loader

LW156FV is a product independently researched and developed by XCMG. It is equipped with national engine, high-quality split type double change, four-wheel drive, full hydraulic steering, strong power, higher efficiency and stronger environmental adaptability.

Parameters of LW156FV Wheel Loader

Item		Short boom	Standard boom	Long boom	Units
Rated load		1200	1100	1000	kg
Tipping load		2400	2200	2000	kg
Unloading height	Bucket flat height	3470	3740	3870	mm
	Standard	3000	3300	3500	mm
Unloading distance		785	830	1070	mm
Rated bucket capacity			0.7		m ³
Overall mass		4450	4550	4650	kg
Wheel base			2300		mm
Tread			1500		mm
Maximum hoisted hinge pin height		3730	3920	4190	mm
Maximum breakout force			44		kN
Maximum traction			40		
Boom hoisting time			5.5		s
Three items and time			9		s
Minimum turning radius (tire center)			4620		mm
Articulation angle			35		°
Climbing capacity			25		°
Minimum ground clearance			260		mm
Tire specification			16/70-16		—
Overall dimensions (length*width*height)		5890*2060*2900	6140*2060*2900	6390*2060*2900	mm
Engine	Model		YN27GBZ		—
	Rated power/speed		55/2400		kW/rpm
Driving speed	First position (drive/back)		8		km/h
	Second position (drive/back)		20.5		km/h