

Engineering & Construction Crane



XCT25L4_Y Truck Crane



- **Product Category:** Truck Crane
- **Brand:** XCMG
- **Model:** XCT25L4_Y
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XCT25L4_Y Truck Crane

XCT25L4_Y is widely used in construction sites, urban reconstruction, transportation, ports, bridges, oil fields, mines and other complex operating environments.

Parameters of XCT25L4_Y Truck Crane

Item			Unit	Parameter
Category	Max. total rated lifting capacity		t	25
	Min. rated working radius		m	3
	Turning radius at turntable tail	Counterweight	mm	3340
		Auxiliary winch	mm	3330
		Base boom	kN.m	1132

	Max. load moment	Fully-extended boom		kN.m	713
		Fully-extended boom + Jib		kN.m	492
	Outrigger span (fully-extended)	Longitudinal		m	5.65
		Lateral		m	6.4
Main performance	Hoist height	Base boom		m	10.2
		Fully-extended boom		m	40.7
		Fully-extended boom + Jib		m	50.2
	Boom length	Base boom		m	10.8
		Fully-extended boom		m	42
		Fully-extended boom + Jib		m	51
	Jib offset angle			°	0, 15, 30
	Elevating time	Boom raising		s	≤35
	Telescoping time	Fully extended/retracted		s	≤95
Working speed	Max. slewing speed			r/min	2.5
	Outrigger extending and retracting time	Outrigger beam	Extending	s	≤25
			Retracting	s	≤20
		Outrigger jack	Extending	s	≤25
			Retracting	s	≤20
	Hoisting speed (single line, 4th layer)	Main winch		m/min	≥135
		Auxiliary winch		m/min	≥135
	Noise	Exterior noise level			dB (A)
Noise level at seated position			dB (A)	≤90	