

Engineering & Construction Crane



XCT30_M Truck Crane



- **Product Category:** Truck Crane
- **Brand:** XCMG
- **Model:** XCT30_M
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XCT30_M Truck Crane

XCT30_M truck crane is widely used for the lifting operations in Oilfields, mines, general engineering projects, such as construction site, urban renewal, communication and transportation, sea ports, bridge construction, desert, and complex working environments.

Parameters of XCT30_M Truck Crane

Item		Unit	Parameter
Dimensions (length x width x height)		mm	12362×2550×3415
Total vehicle mass in travel configuration		kg	30000
Axle load	1st and 2nd axle	kg	6400

	3rd axle	kg	11800
Engine rated power/rpm		kW/(r/min)	192/2200
Max. output torque/rpm		N.m/(r/min)	1000/1400
Max. travel speed		km/h	85
Min. turning diameter		m	20
Min. ground clearance		mm	261
Approach angle		°	16.5
Departure angle		°	13
Max. grade ability		%	40
Fuel consumption per 100 km		L	32
Max. total rated lifting capacity		t	30
Min rated working radius		m	3
Max. load moment	Base boom	kN.m	965
	Fully-extended boom	kN.m	576
Outrigger span	Longitudinal	m	5.23
	Lateral	m	6.4
Hoist height	Base boom	m	10.5
	Fully-extended boom	m	40.3
Boom length	Base boom	m	10.4
	Fully-extended boom	m	40.5
Jib offset angle		°	0、15、30
Boom raising time		s	≤38
Boom fully extending time		s	≤90
Hoisting speed (single line, 4th layer, no load)	Main winch	m/min	≥120
	Auxiliary winch	m/min	≤90