

Engineering & Construction Crane



XCT60_Y Truck Crane



- **Product Category:** Truck Crane
- **Brand:** XCMG
- **Model:** XCT60_Y
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XCT60_Y Truck Crane

XCT60_Y is widely used in construction sites, urban reconstruction, transportation, ports, bridges, oil fields, mines and other complex operating environments.

Parameters of XCT60_Y Truck Crane

Item		Unit	Parameter
Dimensions (length x width x height)		mm	14090×2790×3630
Total vehicle mass in travel configuration		kg	42200
Axle load	1st and 2nd axle	kg	16200
	3rd and 4th axle	kg	26000

Engine rated power/rpm		kW/(r/min)	247/2200
Max. output torque/rpm		N.m/(r/min)	1350/1100-1600
Max. travel speed		km/h	90
Min. turning diameter		m	24
Min. ground clearance		mm	250
Approach angle		°	18/10 (front protective device included)
Departure angle		°	13
Max. grade ability		%	36
Fuel consumption per 100 km		L	36
Max. total rated lifting capacity		t	60
Min rated working radius		m	3
Max. load moment	Base boom	kN.m	2009
	Fully-extended boom	kN.m	1113
Outrigger span	Longitudinal	m	6.1
	Lateral	m	7.1
Hoist height	Base boom	m	11.3
	Fully-extended boom	m	43.6
Boom length	Base boom	m	11.5
	Fully-extended boom	m	44
Jib offset angle		°	0、15、30
Boom raising time		s	≤40
Boom fully extending time		s	≤90
Hoistin Hoisting speed (single line, 4th layer, no load)	Main winch	m/min	≥130
	Auxiliary winch	m/min	≥130