

Aerial Working Platform

XG0607DC Electric Drive Series



- **Product Category:** AERIAL WORKING EQUIPMENT
- **Brand:** XCMG
- **Model:** XG0607DC
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to

Product Feature of XG0607DC Articulating Boom Lifts

The XG0607DC scissor aerial work platform is a new type of aerial work platform developed and produced by XCMG Group. The maximum platform height is 3.6m, the vehicle width is 0.76m, the rated load is 230kg, the platform extension length is 0.6m, and the Max. gradeability is 25%; The machine has compact structure, advanced performance and complete safety protection. It is a special model tailored for construction users. It is pollution-free, green and environmentally friendly, stable in lifting, easy to operate, and easy to maintain. It can be widely used in workshops, warehouses, Various industries, such as airports and stations, are especially suitable for small working environments.

Parameters of XG0607DC Articulating Boom Lifts

Item	Unit	Parameter
Load capacity	kg	240
Load capacity of extended platform	kg	100
Max.Occupant Capacity	—	2
Max.Working height	m	5.6
Max.Platform height	m	3.6
Overall length (no ladder)	mm	1440(1290)
Overall width	mm	760
Overall height (platform folded)	mm	2020 (1660)
Working platform dimension (Length x Width)	mm	1290×700
Length of extension platform	mm	600
Min.ground clearance (pit protector rising/descending)	mm	65/15
Wheel base	mm	1030
Min.turning radius (inner/outer wheel)	m	0.4/1.55
Driving motor	kW	0.45
Lifting motor	kW	1.3
Max.Traveling speed at low level	km/h	4
Max.Traveling speed at high level	km/h	0.5
Lifting/Descending duration of platform	s	27-37/23-33
Max.gradeability	%	25
Tilt warning angle (side/front and rear)	°	1.5/3
Battery	v/Ah	2×12/85
Charger	v/A	24/15
Tire specification	—	254×76
Total machine weight	kg	915