

Aerial Working Platform

XG0607DC(CE) Electric Drive Series



- **Product Category:** AERIAL WORKING EQUIPMENT
- **Brand:** XCMG
- **Model:** XG0607DC(CE)
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to

Product Feature of XGA16E(CE) Articulating Boom Lifts

Effective and energy-saving electric-drive system features zero emission and low noise, together with the traceless tires, enabling this machine easily to work in enclosed environments such as office building, hospitals and schools and minimizing the effect on environment.

Active protective mechanism such as pothole protective mechanism and the self-developed safety control system feature the humanized design and the rich options, meeting the customer needing for safety, reliability and intelligence.

Narrow- structure design enables the complete vehicle to easily pass through a single gateway; foldable fence could make the transportation easie.

Zero Turning Radius "is unique and enable machine to corner in narrow room.

Max. payload at 230kg, leading the industry.

Maximum traveling speed 4.0km/h and 25% gradeability make the driving easier.

Parameters of XGA16E(CE) Articulating Boom Lifts

Item	Unit	Parameter
Load capacity	kg	240
Load capacity of extended platform	kg	100
Max.Occupant Capacity	—	2
Max.Working height	m	5.9
Max.Platform height	m	3.9
Overall length (no ladder)	mm	1290
Overall width	mm	760
Overall height (platform folded)	mm	1660
Working platform dimension (Length x Width)	mm	1290*700
Length of extension platform	mm	600
Min.ground clearance (pit protector rising/descending)	mm	65/15
Wheel base	mm	1030
Min.turning radius (inner/outer wheel)	m	0.4/1.55
Driving motor	kW	0.45
Lifting motor	kW	1.3
Max.Traveling speed at low level	km/h	4
Max.Traveling speed at high level	km/h	0.5
Lifting/Descending duration of platform	s	27~37
Max.gradeability	%	25
Tilt warning angle (side/front and rear)	°	1.5/3
Battery	v/Ah	2×12/75
Charger	v/A	24/15
Tire specification	—	254×76
Total machine weight	kg	900