

# Aerial Working Platform

## XG0607DC(CE) Electric Drive Series



- **Product Category:** AERIAL WORKING EQUIPMENT
- **Brand:** XCMG
- **Model:** XG0607DC(CE)
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to

### Product Feature of XGA16E(CE) Articulating Boom Lifts

1. Effective and energy-saving electric-drive system features zero emission and low noise.
2. Active protective mechanism such as pothole protective mechanism and the self-developed safety control system meeting the customer needing for safety, reliability and intelligence.
3. Narrow- structure design enables the complete vehicle to easily pass through a single gateway; foldable fence could make the transportation easier. "Zero Turning Radius "is unique and enable machine to corner in narrow room.

## Parameters of XGA16E(CE) Articulating Boom Lifts

| Item                                                   | Unit | Parameter |
|--------------------------------------------------------|------|-----------|
| Load capacity                                          | kg   | 240       |
| Load capacity of extended platform                     | kg   | 100       |
| Max.Occupant Capacity                                  | —    | 2         |
| Max.Working height                                     | m    | 5.9       |
| Max.Platform height                                    | m    | 3.9       |
| Overall length (no ladder)                             | mm   | 1290      |
| Overall width                                          | mm   | 760       |
| Overall height (platform folded)                       | mm   | 1660      |
| Working platform dimension (Length x Width)            | mm   | 1290*700  |
| Length of extension platform                           | mm   | 600       |
| Min.ground clearance (pit protector rising/descending) | mm   | 65/15     |
| Wheel base                                             | mm   | 1030      |
| Min.turning radius (inner/outer wheel)                 | m    | 0.4/1.55  |
| Driving motor                                          | kW   | 0.45      |
| Lifting motor                                          | kW   | 1.3       |
| Max.Traveling speed at low level                       | km/h | 4         |
| Max.Traveling speed at high level                      | km/h | 0.5       |
| Lifting/Descending duration of platform                | s    | 27~37     |
| Max.gradeability                                       | %    | 25        |
| Tilt warning angle (side/front and rear)               | °    | 1.5/3     |
| Battery                                                | v/Ah | 2×12/75   |
| Charger                                                | v/A  | 24/15     |
| Tire specification                                     | —    | 254×76    |
| Total machine weight                                   | kg   | 900       |