

Aerial Working Platform

XG1012AC(CE) Electric Drive Series



- **Product Category:** AERIAL WORKING EQUIPMENT
- **Brand:** XCMG
- **Model:** XG1012AC(CE)
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to

Product Feature of XG1012AC(CE) Articulating Boom Lifts

1. Effective and energy-saving electric-drive system features zero emission and low noise.
2. Meeting the customer needing for safety, reliability and intelligence.
3. Narrow- structure design enables the complete vehicle to easily pass through a single gateway.
4. foldable fence could make the transportation easier.
5. "Zero Turning Radius" is unique and enable machine to corner in narrow room.

Parameters of XG1012AC(CE) Articulating Boom Lifts

Item	Unit	Parameter
Load capacity	kg	450
Load capacity of extended platform	kg	115
Max.Occupant Capacity	—	2
Max.Working height	m	10
Max.Platform height	m	8
Overall length (no ladder)	mm	2267
Overall width	mm	1170
Overall height (platform folded)	mm	1805
Working platform dimension (Length x Width)	mm	2270×1120
Length of extension platform	mm	900
Min.ground clearance (pit protector rising/descending)	mm	110/20
Wheel base	mm	1877
Min.turning radius (inner/outer wheel)	m	0/2.3
Driving motor	kW	0.87
Lifting motor	kW	3.3
Max.Traveling speed at low level	km/h	4
Max.Traveling speed at high level	km/h	0.8
Lifting/Descending duration of platform	s	49~60
Max.gradeability	%	25
Tilt warning angle (side/front and rear)	°	1.5/3
Battery	v/Ah	4×6/280
Charger	v/A	24/30
Tire specification	—	381×127
Total machine weight	kg	2680