

# Road Construction & Maintenance Machinery



## XAP123 Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XAP123
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

### Product Feature of XAP123 Soil Stabilizer

XAP123 Asphalt Mixing Equipment is an international advanced product developed independently by XCMG for producing asphalt mixture, modified asphalt mixture, warm-mixing asphalt mixture and others at all levels and be used in supporting with hot recycling equipment and foam asphalt equipment, fully meet the requirements of projects on classified road, municipal road and freight yard.

## Parameters of XAP123 Soil Stabilizer

| Equipment type       |                                                      | Unit           | XAP123                         |
|----------------------|------------------------------------------------------|----------------|--------------------------------|
| Complete machine     | Theoretical rated productivity<br>(5% water content) | t/h            | 100-120                        |
|                      | Temperature accuracy                                 | °C             | ±5                             |
|                      | Total installed power                                | kW             | 337                            |
|                      | Length* width* height                                | m              | 32*26.5*16.5                   |
|                      | Floor area                                           | m <sup>2</sup> | 848                            |
| Cold hopper          | Capacity                                             | m <sup>3</sup> | 4*9                            |
| Drying drum          | Diameter                                             | m              | 1.8                            |
|                      | Length                                               | m              | 7.7                            |
|                      | Fuel                                                 |                | Diesel, heavy oil/ natural gas |
|                      | Drying ability (5% water content)                    | t/h            | 130                            |
| Dust collector       | Bag filter area                                      | m <sup>2</sup> | 480                            |
| Main mixing building | Screen layers                                        |                | 4                              |
|                      | Screening area                                       | m <sup>2</sup> | 14.8                           |
|                      | Capacity of hot aggregate silo                       | m <sup>3</sup> | 12.4                           |
|                      | Weighing capacity of aggregate                       | kg             | 1500                           |
|                      | Weighing capacity of powder                          | kg             | 300                            |
|                      | Weighing capacity of bitumen                         | kg             | 130                            |
|                      | Mixing power                                         | kW             | 2*22                           |

|  |                |    |      |
|--|----------------|----|------|
|  | Mixer capacity | kg | 1750 |
|--|----------------|----|------|