

# Road Construction & Maintenance Machinery



## XAP245H Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XAP245H
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

### Product Feature of XAP245H Soil Stabilizer

XAP245H Asphalt Mixing Equipment is an international advanced product developed independently by XCMG for producing asphalt mixture, modified asphalt mixture, warm-mixing asphalt mixture and others at all levels and be used in supporting with hot recycling equipment and foam asphalt equipment, fully meet the requirements of projects on classified road, municipal road and freight yard.

## Parameters of XAP245H Soil Stabilizer

| Item                                                        | Unit               | Parameter    |
|-------------------------------------------------------------|--------------------|--------------|
| Rated productivity                                          | t/h                | 240          |
| Mixing capacity                                             | kg/patch           | 3500         |
| Metering accuracy                                           |                    |              |
| Asphalt                                                     | %                  | 0.2          |
| Powder                                                      | %                  | 0.3          |
| Aggregate                                                   | %                  | 0.3          |
| Aggregate grades                                            | -                  | -            |
| Fuel consumption                                            | kg/t               | 6.5          |
| Dust emission concentration                                 | mg/Nm <sup>3</sup> | 40           |
| Asphalt fume                                                | mg/m <sup>3</sup>  | 30           |
| Nitric oxide                                                | mg/m <sup>3</sup>  | 200          |
| Sulfur dioxide                                              | mg/m <sup>3</sup>  | 200          |
| Carbon monoxide                                             | mg/m <sup>3</sup>  | 1000         |
| Blackness of exhaustion (Ringelman class)                   | -                  | ≤I           |
| Total power                                                 | kW                 | 760          |
| Maximum single power                                        | kW                 | 160          |
| Floor area                                                  | m <sup>2</sup>     | 2100 (50×42) |
| Thermal oilfurnace heating capacity                         | kcal/h             | -            |
| Optional finished product bin volume (m)                    |                    |              |
| Optional dual-fuel burner,gas burner, light and heavy oil b | -                  | -            |