

Aerial Working Platform

XGA20E(CE) Articulating Boom Lifts



- **Product Category:** Articulating Boom Lifts
- **Brand:** XCMG
- **Model:** XGA20E(CE)
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XGA20E(CE) Articulating Boom Lifts

With working height from 8 to 22m, Truforce 16m towable cherry picker man lift low price articulating boom lift is designed with outstanding working platform and intuitive control to allow operators to efficiently where they need to go.

While providing excellent versatility for a variety of jobs, and suitable for all working environments, this type of articulating boom is lightweight, easy transport, and cost effective, compared with the self-propelled one.

Parameters of XGA20E(CE) Articulating Boom Lifts

Item	Unit	Parameter
Max. Working Height	m	20.63
Max. Platform Height	m	18.63
Max. Working Range	m	12.08
Max. Load Capacity	kg	256/350
1st Boom luffing Range	°	0~+72
2nd Boom luffing Range	°	0~+73
Fly Jib Luffing Range	°	-65~+70
Rotation Angle of Turntable	°	360
Rotation Angle of Platform	°	160
Max. Tail Wagging	mm	540
Max. Travel Speed	km/h	5.5
Min. Turning Radius	m	2.3
Min. Ground Clearance	mm	330
Max. Grade Ability	%	45
Tire Specification	-	36X14-20 ; 355/55D625
Engine Model	-	Kubota V2403
Rated Power of Engine	kW/ (r/min)	36.8Kw
Battery Specification(V/Ah)		
Main Motor Specification(kw/V)		
Drive Motor Specification(kw/V)		
Total Weight	kg	9900
Platform Size	mm	1830×760×1150
a Overall Length	mm	8520
b Overall Width	mm	2300
c Overall Height	mm	2400
d Wheel Base	mm	2500