

Road Construction & Maintenance Machinery



XLZ2103S Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XLZ2103S
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XLZ2103S Soil Stabilizer

XLZ2103S road cold recycling machine is a multifunctional road maintenance machine mainly used for the upgrade operations of the used asphalt county and township roads as well as the in-site stabilized soil mixing operations. XLZ2103S road cold recycling machine is applicable for the mixing of natural soil with filler, cement, and lime to improve the mechanical and physical performances of the soil and for the milling operations of damaged asphalt or asphalt concrete roads in thickness of no higher than 150mm. In addition, it's also applicable for the in-situ stabilized soil mixing operations for the substrates and roadbeds of the highway, urban road, square, harbor, and parking lot projects.

Parameters of XLZ2103S Soil Stabilizer

Item	Unit	XLZ2103S
Milling width	mm	2100
Maximum milling depth	mm	400
Cutter spacing	mm	18
Diameter of milling wheel (with cutter)	mm	1380
Manufacturer		Weichai
Model		WP13G530E310
The quantity of cylinder stator		6
Rated power	kW	353
Engine speed	rpm	2100
Oil consumption: Full load	kg/h	69.86
Working speed	km/h	0-3.2
Traveling speed	km/h	0-23
Theoretical gradeability (working gear)	%	20
Ground clearance	mm	350
Front axle load	kg	16000
Rear axle load	kg	5500
Shipping weight	kg	21000
Working weight	kg	21000
Fuel tank	L	650
Hydraulic oil tank	L	380
Water tank	L	1000
Voltage of electric system	V	24
Machinery(length*width*height)	mm	9232x3162x3450