

Road Construction & Maintenance Machinery



XLZ2303S Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XLZ2303S
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XLZ2303S Soil Stabilizer

XLZ2303S road cold recycling machine is a multifunctional road maintenance machine mainly used for the upgrade operations of the used asphalt county and township roads as well as the in-site stabilized soil mixing operations. XLZ2303S road cold recycling machine is applicable for the mixing of natural soil with filler, cement, and lime to improve the mechanical and physical performances of the soil and for the milling operations of damaged asphalt or asphalt concrete roads in thickness of no higher than 150mm. In addition, it's also applicable for the in-situ stabilized soil mixing operations for the substrates and roadbeds of the highway, urban road, square, harbor, and parking lot projects.

Parameters of XLZ2303S Soil Stabilizer

Item	Unit	Parameter
Manufacturer	-	Weichai
Engine Model	-	WP13G530E310
Rated power/speed	kW/rpm	390
Working speed	km/h	0-3.2/4
Traveling speed	km/h	0-22.8/29
Theoretical gradeability	%	≥20
Ground clearance	mm	350
Working weight	kg	26500/22500
Maximum Milling width	mm	2100/2300
Maximum milling depth	mm	400
Amount of tools pcs	-	162
Rotor diameter	mm	1380
Overall dimensions	mm	9232*3262*3450
Fuel tank	L	650
Hydraulic oil tank	L	380
Water tank	L	1000