

Road Construction & Maintenance Machinery



XTF1003 Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XTF1003
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XTF1003 Soil Stabilizer

XTF1003 asphalt synchronous chip sealer can realize the synchronous spreading of asphalt and gravel, improve the quality of pavement seal coat; It can be used to spread rubber asphalt, matrix asphalt, modified asphalt and emulsified asphalt; It is applicable to the construction of lower and upper seal coat, wearing course construction for new and old road surface, layer spread method of asphalt pavement, the separate spreading of asphalt and gravel in special case, etc.; It can not only be used for the interlayer treatment and medium maintenance construction of high-grade highway, but also can be used for the construction of rural roads with less traffic.

Parameters of XTF1003 Soil Stabilizer

Item	Unit	Parameter
Maximum seal width	m	4
Asphalt spraying amount	Kg/m ²	0.2-3.0
Gravel quantity	L/m ²	3.22
Distributing accuracy	%	±1.5
Capacity of asphalt tank	m ³	6
Gravel silo volume	m ³	10
Gravel diameter	mm	3.25
Working speed	km/h	3.10
Chassis model	-	HOWO ZZ1257N4347E1(China-5)
Engine type	-	D10.31-50
Engine power	kW/r/min	228/1900
Driving mode	-	6×4
Maximum traveling speed	km/h	80
Diesel tank volume (chassis)	L	-
Diesel tank volume (work device)	L	-