

Road Construction & Maintenance Machinery



XTF1203 Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XTF1203
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XTF1203 Soil Stabilizer

XZJ5313TFCTB (XTF1203) asphalt synchronous chip sealer can realize the synchronous spreading of asphalt and gravel, improve the quality of pavement seal coat; It can be used to spread rubber asphalt, matrix asphalt, modified asphalt and emulsified asphalt; It is applicable to the construction of lower and upper seal coat, wearing course construction for new and old road surface, layer spread method of asphalt pavement, the separate spreading of asphalt and gravel in special case, etc.; It can be used for the interlayer treatment and medium maintenance construction of high-grade highway.

Parameters of XTF1203 Soil Stabilizer

Item	Unit	Parameters
Product model	-	XZJ5213TFCTB (XTF1203)
Working performance parameter		
Maximum seal width	m	4
Asphalt spraying amount	kg/m ²	0.2-3.0
Gravel quantity	L/m ²	3-22
Capacity of asphalt tank	m ³	6
Gravel silo volume	m ³	14
Working speed	km/h	3 -10
Chassis performance parameter		
Chassis brand	-	HOWO
Engine type	-	D10.34 -50
Engine power	kW/r/min	249/1900
Driving mode	-	8*4
Max. travelling speed	km/h	90
Curb weight	kg	25300
Diesel tank capacity	L	300
Total mass	kg	31000
Overall dimension parameter		
Overall dimension	mm	11980×2500×3890
Min. ground clearance	mm	243