

# Road Construction & Maintenance Machinery



## XTF1403R Soil Stabilizer



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XTF1403R
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

### Product Feature of XTF1403R Soil Stabilizer

XZJ314TFCTB (XTF1403R) asphalt synchronous chip sealer can realize the synchronous spreading of asphalt and gravel, improve the quality of pavement seal coat; It can be used to spread rubber asphalt, matrix asphalt, modified asphalt and emulsified asphalt; It is applicable to the construction of lower and upper seal coat, wearing course construction for new and old road surface, layer spread method of asphalt pavement, the separate spreading of asphalt and gravel in special case, etc.; It can not only be used for the interlayer treatment and medium maintenance construction of high-grade highway, but also can be used for the construction of rural roads with less traffic.

## Parameters of XTF1403R Soil Stabilizer

| Item                             | Unit              | Parameter                     |
|----------------------------------|-------------------|-------------------------------|
| Maximum seal width               | m                 | 4                             |
| Asphalt spraying amount          | Kg/m <sup>2</sup> | 0.2-3.0                       |
| Gravel quantity                  | L/m <sup>2</sup>  | 3-22                          |
| Distributing accuracy            | %                 | ±1.5                          |
| Capacity of asphalt tank         | m <sup>3</sup>    | 8                             |
| Gravel silo volume               | m <sup>3</sup>    | 14                            |
| Gravel diameter                  | mm                | 3-25                          |
| Working speed                    | km/h              | 3-10                          |
| Chassis model                    | -                 | HOWO ZZ1317N4667E1H (China-V) |
| Engine type                      | -                 | D10.38-50                     |
| Engine power                     | kW/r/min          | 276/2100                      |
| Driving mode                     | -                 | 8×4                           |
| Maximum traveling speed          | km/h              | 102                           |
| Diesel tank volume (chassis)     | L                 | -                             |
| Diesel tank volume (work device) | L                 | -                             |