

Fire & Rescue Vehicle



JP20C2 Water and Foam Towers Fire Truck



- **Product Category:** Fire-Fighting Machinery
- **Brand:** XCMG
- **Model:** JP20C2
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of JP20C2 Water and Foam Towers Fire Truck

JP20C2 is equipped with a Heavy truck HOWO ZZ5347V4647E5 two class automotive chassis. It is a multi-function main battle truck combining water-tank, high-spraying and foam together, which is applicable for fire extinguishment in low rise buildings in city, industrial and mining enterprises and petrochemical engineering enterprises, oil tank, warehouse and etc..

- **Powerful fire fighting ability:** it is equipped with Heavy truck 2-row cab HOWO chassis, which can carry 6 persons and is suitable for marshaling fire fighting.
- **Complete in fire system configuration:** the tank capacity of car carbon steel tank is 13900kg, of which 11800kg water tank, foam tank 2100kg.
- **Convenient and efficient operation, high security:** upper booms, turntables, water monitor action and pump rotary speed are all under centralized control. 360 ° continuous rotation,

hydraulic drive, high operating efficiency, security and comfort; Then 40m wired remote control, more suitable for inflammable and explosive fire operations, better guarantee the life safety of firefighters.

- Humanization design, multiple security protection settings, high intelligence degree.

Parameters of JP20C2 Water and Foam Towers Fire Truck

Item	Unit	Parameter
Overall length	mm	10620
Overall height	mm	3880
Overall width	mm	2500
Total weight	kg	32250
Extinguishant rated load weight		
Water	kg	11800
Foam	kg	2100
Dry powder	kg	-
Max. travel speed	km/h	≥90
Max. net power	kW	274
Rated working height	m	20
Max. working radius	m	12
Time for deploying boom	s	≤45
Time for deploying outriggers	s	≤20
Monitor		
Water monitor rated flow	L/s	≥64
Water monitor rated reach	m	≥60
Water pump		
Fire rated flow	L/s	≥60
Fire rated pressure	MPa	≥1.2