

Fire & Rescue Vehicle



JP20G1 Water and Foam Towers Fire Truck



- **Product Category:** Fire-Fighting Machinery
- **Brand:** XCMG
- **Model:** JP20G1
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of JP20G1 Water and Foam Towers Fire Truck

With a firefighting liquid and foam device added on a water and foam towers fire truck, JP20G1 water tower fire truck Integrates functions of a water-tank truck, a foam truck, and a water tower fire truck into one unit, and is mainly used for firefighting in low-rise buildings of towns and industrial & mining enterprises, and In buildings of petrochemical enterprises, oil tanks, warehouses, and so on.

- According to actual firefighting requirements, JP20/G1 is equipped with an Independent crew room with 4 seats, which is suitable for centralized delivery of firefighting groups. In the crew room, the air conditioning system, professional fire seats and intercom system are equipped.
- Intelligent control brings convenience and efficiency. Operations in the superstructure are all controlled in the chassis. The vehicle is equipped with a control panel of new type and explosive fire protection, and can better guarantee the life safety of fire fighters.

upgraded family appearance and a 7 inch display, so the firefighting system's working state can be clearly displayed in real time. With the functions of one-button water spraying, foam spraying, foam external supply, and flushing equipped, the vehicle's operating axis are simple.

- Wired remote control is safe and reliable. JP20/G1, equipped with 25m cable remote control box, 4-Inch display, one-button firefighting control, can display the working status in real-time. Is more suitable for firefighting in flammable and explosive fire site, and can better guarantee the life safety of fire fighters.
- All aluminum alloy frame structure: light weight and strong corrosion resistance.

Parameters of JP20G1 Water and Foam Towers Fire Truck

Item	Unit	Parameter
Overall length	mm	12000
Overall height	mm	4000
Overall width	mm	2550
Total weight	kg	42680
Extinguishant rated load weight		
Water	kg	17000
Foam	kg	3000
Dry powder	kg	-
Max. travel speed	km/h	≥90
Max. net power	kW	405
Rated working height	m	20
Max. working radius	m	15
Time for deploying boom	s	≤70
Time for deploying outriggers	s	≤30
Monitor		
Water monitor rated flow	L/s	≥120
Water monitor rated reach	m	≥80
Water pump		
Fire rated flow	L/s	≥170
Fire rated pressure	MPa	≥1