

Fire & Rescue Vehicle



JP62S1 Water and Foam Towers Fire Truck



- **Product Category:** Fire-Fighting Machinery
- **Brand:** XCMG
- **Model:** JP62S1
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of JP62S1 Water and Foam Towers Fire Truck

JP62S1 uses FMX540 national-V chassis. It combines water-tank, high-spraying and foam truck together with large specific power and great acceleration performance, fit for middle-high rise buildings in city, mining, oil field and warehouse. It has intelligent equipment such as fire monitor, one-key water-fetching and remote control.

- Innovative overall arrangement, outstanding overall performance. A K-structure is equipped in its undercarriage. Its upper booms are consisted of 3+3+1 fold booms, which enable 36m operation scale.
- Strong power and excellent fire-extinguishing performance. It is equipped with a 540hp chassis, an imported 10000L/Min fire pump, an 7200L/Min fire monitor, aluminium alloy large-bore pipelines, whose liquid load is 7500kg.
- The automatic control technology based on the multistage expansion of the leg makes the arm movement safer, more stable and more rapid.

Parameters of JP62S1 Water and Foam Towers Fire Truck

Item	Unit	Parameter
Overall length	mm	12780
Overall height	mm	3890
Overall width	mm	2500
Total weight	kg	41750
Extinguishant rated load weight		
Water	kg	4200
Foam	kg	3300
Dry powder	kg	-
Max. travel speed	km/h	≥85
Max. net power	kW	397
Rated working height	m	62
Max. working radius	m	36
Time for deploying boom	s	≤170
Time for deploying outriggers	s	≤30
Monitor		
Water monitor rated flow	L/s	≥120
Water monitor rated reach	m	≥80
Water pump		
Fire rated flow	L/s	≥170
Fire rated pressure	MPa	≥1