

Fire & Rescue Vehicle



JP72S5 Water and Foam Towers Fire Truck



- **Product Category:** Fire-Fighting Machinery
- **Brand:** XCMG
- **Model:** JP72S5
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of JP72S5 Water and Foam Towers Fire Truck

JP72S5 water and foam towers fire truck is equipped with a Volvo FM540 national-V chassis, the rated power is 398KW, having power density and good mobility. It is equipped with large flow HALE 8FGF fire pump and AKRON 3480 + 5178 fire monitor. With 5tonsof liquid volume, ithas outstanding fire performance. The truck is equipped with fire monitoring, one-key water taking, remote control and other Intelligent equipment.

- Innovative overall arrangement, outstanding overall performance. A K-structure Is equipped in its undercarriage. Its upper booms are consisted of 4+3+1 fold booms, which enable 33m operation scale. The scale controlling technology based on multiple telescoping outriggers enables boom moves safer, stabler and faster.
- Strong power and excellent fire-extinguishing performance. It is equipped with a 540hp chassis, an imported 10000L/Min fire pump, an 7200L/Min fire monitor, aluminium alloy

large-bore pipelines, whose liquid load is 5000kg.

- It is equipped with the automatic amplitude control technology based on the multi-stage expansion of the legs, so the cantilever crane movements are safer, more stable and faster.

Parameters of JP72S5 Water and Foam Towers Fire Truck

Item	Unit	Parameter
Overall length	mm	12940
Overall height	mm	3950
Overall width	mm	2500
Total weight	kg	42680
Extinguishant rated load weight		
Water	kg	2850
Foam	kg	2100
Dry powder	kg	-
Max. travel speed	km/h	≥85
Max. net power	kW	397
Rated working height	m	72
Max. working radius	m	33
Time for deploying boom	s	≤200
Time for deploying outriggers	s	≤40
Monitor		
Water monitor rated flow	L/s	≥120
Water monitor rated reach	m	≥80
Water pump		
Fire rated flow	L/s	≥170
Fire rated pressure	MPa	≥1