



XE150WB Wheel Excavator



- **Product Category:** Excavator
- **Brand:** XCMG
- **Model:** XE150WB
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XE150WB Wheel Excavator

XCMG XE150WB wheel excavator is powerful, flexible and exquisite enough to cope with a variety of working conditions. The appearance size of the machine complies with road regulations and transportation requirements. It plays an important role in the aspects of airport, port, oil field, urban construction, irrigation and water conservancy and rapid repair, and brings rich value returns for customers.

XCMG XE150WB wheel excavator has used a new generation of independent researched and developed controllers as well as a low-noise pump and especially considered the matching between the engine and the low-speed load to make full use of the engine power, improve the working efficiency and effectively reduce the fuel consumption.

Advantages and Highlights:

1. Equipped with a new generation of high-efficiency direct injection engine.
2. Using highly professional design and analysis tools, combined with bench tests, to ensure that our machines are strong and durable.
3. The highest breakout force on the loading end is leading the industry by 15%~20% compared with like models.
4. Fully functional, ergonomically designed man-machine driving and driving environment, equipped with high intensity cab certified with ROPS.

Parameters of XE150WB Wheel Excavator

Engine model	/	QSB4.5
Output power of engine	Kw/r/min	104/2000
Max.torque/engine	N.m	586
Displacement	L	4.5
Fuel tank capacity	L	250
Rated flow of main pump	L/min	2x160
Pressure of main safety valve	Mpa	31.4/34.3
Hydraulic tank capacity	L	135
Slewing speed	r/min	13.7
Digging capacity of tcuket	KN	60
Digging capacity of tcuket rod	KN	65
Min.turning radius	mm	6500
Travel speed	Km/h	
Gradient capability	%	70
A Total length	mm	6482
B Total width	mm	2552
C Total heighth	mm	3158
Counterweight ground clearance	mm	1230
Min.ground clearance	mm	359
Min.tail swing radius	mm	2300
Wheelbase	mm	2800
Track gauge	mm	1920
Total width of chassis	mm	2495
Distance between front axle and turning center	mm	1700
Hood height	mm	2430
The maximum digging depth of dozer	mm	112