



XE55U Crawler Excavator



- **Product Category:** Excavator
- **Brand:** XCMG
- **Model:** XE55U
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XE55U Crawler Excavator

The XE55U engine meets the T4F emission standards with Exhaust Gas Recycle (EGR), Diesel Oxidation Catalytic converter (DOC) and Diesel Particulate Filter (DPF) technology offering both sufficient power and low fuel consumption. It will always meets your high demands in various jobsites with its compact tail swing, variable angle boom of 70° and 53° for left and right.

Parameters of XE55U Crawler Excavator

Sales model		XE55U
Operating weight		5700
Bucket capacity		0.16
Engine	Model	V2403-CR-E5B
	Direct injection	√
	Four strokes	√
	Water cooling	√
	Turbo-charging	/
	No. of cylinders	4
	Rated power	31.2/2200
	Maximum torque/speed	159.8 / 1500
	Displacement	2.434
Main performance	Travel speed	4.6/2.8
	Swing speed	9.5
	Gradeability	≤35
	Ground pressure	32
	Bucket digging force	44.5
	Arm digging force	24.3
	Maximum tractive force	52.8
Hydraulic system	Rated flow of main pump	158.4
	Main safety valve pressure	30
	Travel system pressure	30
	Swing system pressure	24
	Pilot system pressure	3.5
Oil Capacity	Fuel tank capacity	68
	Hydraulic tank capacity	46
	Engine oil capacity	9.5
Appearance size	Overall length	5340
	Overall width	1960
	Overall height	2555
	Width of platform	1830
	Track length	2490
	Overall width of chassis	1960
	Track width	400
	Wheel base of crawler	1990
	Track gauge	1560
	Counterweight clearance	637
	Min. ground clearance	315
	Min. tail swing radius	2430
	Track height	550
Working scope	Max. digging height	5650
	Max. dumping height	4010

Working scope	Max. digging depth	3640
	Maximum depth cut for 2240mm(8 ft) level bottom	3200
	Max. vertical wall digging depth	2690
	Max. digging radius	6110
	Min. swing radius	1040
Standard	Length of boom	2850
	Length of arm	1570
	Bucket capacity	0.16
Optional	Length of boom	/
	Length of arm	/
	Bucket capacity	/