



XE75U Crawler Excavator



- **Product Category:** Excavator
- **Brand:** XCMG
- **Model:** XE75U
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XE75U Crawler Excavator

The XE75U hydraulic excavator is highly applicable for hydropower, transportation, municipal, garden, farmland reconstruction, oil pipeline and other small-scale construction. Designed features: suitable for suburban and narrow space; ambient temperature: $-15^{\circ}\text{C} \sim 40^{\circ}\text{C}$; Working objects: soil below grade III and loose materials.

Parameters of XE75U Crawler Excavator

Sales model		XE75U
Operating weight		7460
Bucket capacity		0.18~0.3
Engine	Model	V2607-CR-TIE4B
	Direct injection	√
	Four strokes	√
	Water cooling	√
	Turbo-charging	√
	No. of cylinders	4
	Rated power	45/2200
	Maximum torque/speed	225.8/1400-1800
	Displacement	2.615
Main performance	Travel speed	5.4/2.9
	Swing speed	10
	Gradeability	≤35
	Ground pressure	33.5
	Bucket digging force	57
	Arm digging force	38
	Maximum tractive force	68.3
Hydraulic system	Rated flow of main pump	176
	Main safety valve pressure	26.5
	Travel system pressure	26.5
	Swing system pressure	18.6
	Pilot system pressure	3.5
Oil Capacity	Fuel tank capacity	130
	Hydraulic tank capacity	76
	Engine oil capacity	10
Appearance size	Overall length	6150
	Overall width	2230
	Overall height	2685
	Width of platform	2070
	Track length	2825
	Overall width of chassis	2200
	Track width	450
	Wheel base of crawler	2195
	Track gauge	1750
	Counterweight clearance	795
	Min. ground clearance	380
	Min. tail swing radius	1800
	Track height	644
Working scope	Max. digging height	7085
	Max. dumping height	5160

	Max. digging depth	4015
	Maximum depth cut for 2240mm(8 ft) level bottom	/
	Max. vertical wall digging depth	2916
	Max. digging radius	6240
	Min. swing radius	1820
	Length of boom	3720
Standard	Length of arm	1622
	Bucket capacity	0.3
Optional	Optional	Optional
	Optional	Optional
	Optional	Optional